

TD Lighting Solutions

X-ML17052NC-4080-NF2W757GRT-V3-48

Linear Series

www.**tlsteknoloji**.com

PRODUCT PHOTO



SPECIFICATIONS

- Default driving method is constant current input.
- CCT Range from 2700°K up to 6500°K
- Luminous flux range from 4019 lm to 7291 lm
- Efficacy of the module up to 174 lm/W
- CRI 80 is standart
- Outstanding system color tolerance MacAdam 3 over the full operating area
- Simple installation (e.g. screw)
- Long life-time > 60,000 hours
- 5 years guarantee at specified conditions

For your orders please call us:
+90 444 27 33

APPLICATIONS

High Bay Lighting | Low Bay Lighting | Street Lighting

PHOTOMETRY



W/O LENS | TLS16NI-5050-30 | TLS16NI-5050-60 | TLS16NI-5050-90 | TLS16NI-5050-143x67 | TLS16NI-5050-157x75

All Rights Reserved for TLS Technology Systems | Subject to Change with out Prior Notice.
Akçaburgaz Mahallesi 3080. Sokak No:5 Esenyurt / İstanbul | www. tlsteknoloji.com | TEL: +90 444 27 33

TECHNICAL DATA

Beam Angle	116°
Ambient temperature range	-25° ~ +55°C
Tc max	85°C
Max. DC forward current	1400mA
Typical voltage of LED Module at max current	38V
Insulation test voltage	2kV
ESD classification	Class 1
Risk group (EN 62471:2008)	1
Type of protection	IP00

ORDERING INFORMATIONS



All Rights Reserved for TLS Technology Systems | Subject to Change with out Prior Notice.

DRIVING CURRENT VS LUMEN OUTPUT SPECIFICATION

Common Characteristic [@Tj : 85°C] ;				
LED Brand & Type	X-ML17052NC-4080-NFxx-48		Electrical Connection	
PCB Material	ALU			
Operating Temperature (°C)	-40 ~ +85		Parallel	8
Storage Temperature (°C)	-40 ~ +55		Series	6
Thermal Conductivity (W/m-K)	1>		LED Quantity	48
LED	**NC-NF2W757GRT-V3**			
Correlated Color Temperature (CCT)	**4000K**			
Color Rendering Index (CRI)	80+			
Module Operating Voltage (V)	33	35		37
Module Operating Current (mA)	700	1050		1400
Branch Operating Current (mA)	88	131		175
Module Power (W)	23	37		52
Module Light Output (lm)	4019	5664		7291
Module Efficiency (lm/W)	174	155		140

The table below shows how to Module Light Output changes depending on CCT (°K)

	Lumen Output Multiplier				
LED	2700°K (CRI 80)	3000°K (CRI 80)	4000°K (CRI 80)	5000°K (CRI 80)	6500°K (CRI 80)
NC-NF2W757GRT-V3	0,875	0,916	1	1	1

Relative luminous intensity versus CCT (°K)

DATASHEET
X-ML17052NC-4080-NF2W757GRT-V3-48
TD Lighting Solutions

All Rights Reserved for TLS Technology Systems | Subject to Change with out Prior Notice.
Akçaburgaz Mahallesi 3080. Sokak No:5 Esenyurt / İstanbul | www. tlsteknoloji.com | TEL: +90 444 27 33

X-ML17052NC-4080-NF2W757GRT-V3-48 MECHANICAL DRAWINGS



SERBEST ÖLÇÜ TOLERANSLARI -DIN 2768-1 / General Tolerances for linear and angular dimensions (DIN ISO 2768-1)											
0.5 up to 3mm	± 0.1	over 3 up to 6mm	± 0.1	over 6 up to 30mm	± 0.2	over 30 up to 120mm	± 0.3	over 120 up to 400mm	± 0.5	over 400 up to 1000mm	± 0.8

Stock code No : XXXX	MALZEME (MATERIAL) PC	AGIRLIK (WEIGHT)	
Revision : 00			
Date: 13.11.2018	PARÇA NO (PART NO) XXXXX	ÖLÇEK / SCALE	A4
Sheet : 1			
Drawn By: O. ALTUN		TD Lighting Solutions	
Checked By: O. SANATSEVER			
Approved By: M. CINAR			

TLS Teknoloji Sanayi ve Dis Ticaret A.S This drawing is our property. It cant be reproduced or communicated without our written agreement.

All Rights Reserved for TLS Technology Systems | Subject to Change with out Prior Notice.

CCT AND BINNING INFORMATION



All Rights Reserved for TLS Technology Systems | Subject to Change with out Prior Notice.

LIFETIME PROJECTION & WORST CONDITION PERFORMANCE

MODEL NUMBER: **NF2W757GRT-V3**

Test Summary:

Data Set	Case Temperature [°C]	Ambient Temperature [°C]	Drive Current [mA]	Lumen maintenance at 10K hours [%]	Chromaticity Shift (Δu'v') at 10K hours	TM-21 Projection L_{70}(10K) [hours]	TM-21 Projection L_{80}(10K) [hours]	TM-21 Projection L_{90}(10K) [hours]
1	55	> 50	100	98.1	0.0014	> 60600	> 60600	> 60600
2	55	> 50	150	98.3	0.0017	> 60400	> 60400	> 60400
3	55	> 50	200	98.2	0.0020	> 60500	> 60500	48300
4	85	> 80	100	96.4	0.0014	> 60600	> 60600	52500
5	85	> 80	150	96.3	0.0020	> 60400	> 60400	38800
6	85	> 80	200	93.9	0.0035	55900	35300	17100
7	105	> 100	100	92.3	0.0019	> 60600	43700	15500
8	105	> 100	150	93.4	0.0027	> 60400	57800	21000
9	105	> 100	200	90.7	0.0034	42800	26200	11600

All Rights Reserved for TLS Technology Systems | Subject to Change with out Prior Notice.

LEGAL NOTICE

Product information provided by TLS Teknoloji Sistemleri San ve Dış Tic AŞ ("TLS") in this document is believed to be correct and accurate. TLS reserves the right to change/correct the specifications and other data or information relating to products without notice but TLS accepts no liability for errors that may appear in this document, howsoever occurring, or liability arising from the use or application of any information or data provided herein. Neither the supply of such information, nor the purchase or use of products conveys any licence or permission under patent, copyright, trademark or other intellectual property right of TLS or third parties.

Products sold by TLS are subject to its standard Terms and Conditions of Sale that are available on request. No warranty is given that products do not infringe the intellectual property rights of third parties, and furthermore, the use of products in certain ways or in combination with TLS, or non-TLS furnished equipments/components may infringe intellectual property rights of TLS.

The purpose of this document is to provide information only and it may not be used, applied or reproduced (in whole or in part) for any purpose nor be taken as a representation relating to the products in question. No warranty or guarantee express or implied is made concerning the capability, performance or suitability of any product, and information concerning possible applications or methods of use is provided for guidance only and not as a recommendation. The user is solely responsible for determining the performance and suitability of the product in any application and checking that any specification or data it seeks to rely on has not been superseded.

Products are intended for normal commercial applications. For applications requiring unusual environmental requirements, extended temperature range, or high reliability capability (e.g. military, or medical applications), special processing/testing/conditions of sale may be available on application to TLS.

CONTACT

TLS Teknoloji Sistemleri San ve Dış Tic AŞ
Akçaburgaz Mahallesi 3080. Sokak No:5 Esenyurt / İstanbul / TURKEY

info@tlsteknoloji.com
+90 444 27 33

All Rights Reserved for TLS Technology Systems | Subject to Change with out Prior Notice.