

DAISY-2X2-WW

~80° wide beam

TECHNICAL SPECIFICATIONS:

Dimensions	79.5 mm
Height	21 mm
Fastening	pin, screw, clips
ROHS compliant	yes 

MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
C16862_DAISY-2X2-WW	Multi-lens	PMMA	clear	
C16866_DAISY-2X2-SHD	Shade	PC	black	gloss


ORDERING INFORMATION:

Quantities for one set:

Multi-lens	1
Shade	1





Component		Qty in box	MOQ	MPQ	Box weight (kg)
C16862_DAISY-2X2-WW » Box size: 400 x 300 x 300 mm	Multi-lens	440	440	20	5.0
C16866_DAISY-2X2-SHD » Box size: 400 x 300 x 300 mm	Shade	186	440	20	4.8





PHOTOMETRIC DATA (MEASURED):



LED NF2W757G-MT (Tunable White)
FWHM 79.0°
Efficiency 86 %
Peak intensity 0.562 cd/lm
LEDs/each optic 1
Light colour Tunable White
Required components:
C16866_DAISY-2X2-SHD




LED LM28xB Series
FWHM 77.0°
Efficiency 88 %
Peak intensity 0.610 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C16866_DAISY-2X2-SHD




PHOTOMETRIC DATA (SIMULATED):




LED XD16
FWHM 77.0 + °
Efficiency 84 %
Peak intensity 0.640 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C16866_DAISY-2X2-SHD



LED NF2W757G-MT (Tunable White)
FWHM 76.0 + 78.0°
Efficiency 90 %
Peak intensity 0.670 cd/lm
LEDs/each optic 2
Light colour Tunable White
Required components:
C16866_DAISY-2X2-SHD



LED NF2W757G-MT (Tunable White)
FWHM 76.0°
Efficiency 90 %
Peak intensity 0.660 cd/lm
LEDs/each optic 4
Light colour Tunable White
Required components:
C16866_DAISY-2X2-SHD



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salu, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)